

Patch Cord

WST-C-xxxxx-xxxxx



Features:

- High return loss, low Insertion Loss.
- High reliability and stability.
- Excellent Repeatability.
- Meet Telcordia Standard.

Specification:

- Telecommunication system.
- Testing Equipment.
- LAN system.
- Long haul Telecommunications.
- CATV Systems.

Performance Specification

Item	Optical-Fiber Pigtail / Patchcords		
	FC, LC, SC type		FC/APC, SC/APC type
Mode Type	SM	MM	SM
Typical Insertion Loss, dB	0.15	0.3	0.3
Max. Insertion Loss, dB	0.25	0.4	0.5
Typical Backreflection, dB	50	-	62
Min. Backreflection, dB	48	-	60

Order information

WST-C - -

Connector1

S: SC F: FC
M: MTRJ L: LC
T: ST X= Others

Connector2

S: SC F: FC
M: MTRJ L: LC
T: ST X= Others 50/125

Polish type

blank: PC-PC U: UPC-UPC
A: APC-APC B: PC-APC
C: APC-PC X= Others

Fiber type

3: 50/125 (OM3) 4: 50/125 (OM4)
5: 50/125um (OM2) 6: 62.5/125um (OM2)
9: 9/125um (SMF) X= Others

Cable type

S-Simplex D-Duplex

Cable size

B: bare fiber 9: 0.9mm
8: 1.8mm Blank for simplex or duplex: 2.0mm
3: 3.0mm

Jacket type

R-OFNR P-OFNP
L-LSZH V-PVC

Length

001: 1M 010: 10M
030: 30M 01K: 1KM
00A: 0.5M

Modification History

Revision	Date	Description	Originator	Review	Approved
V1.0	02-Sep-18	New Issue	Ivy Chen	Wayne Liao	Wayne Liao



Taipei Headquarters
16F-5, No. 75, Sec. 1,
Xintai 5th Rd., Xizhi Dist.,
New Taipei City 22101,
Taiwan
Tel: +886-2-2698-7208
Fax: +886-2-2698-7210

U.S. Branch
2080 Rancho Higuera Ct.
Fremont, CA 94539,
USA
Tel: 510-651-7800
Fax: 510-651-7822

ShenZhen Branch
610#, 6F, No.204
Building, 2nd Industrial
zone Nanyou, Nanshan
district, Shenzhen,
Guangdong China 518054
Tel: +86-755-86265980
Fax: +86-755-26642741

All specification data are accurate on the date of publication for product comparisons and ordering information. WaveSplitter Technologies, Inc. reserves the right to change specifications without notice.